

Industrial Vacuums

STANDARD VACUUMS



Heavy-Duty Industrial Vacuum



Heavy-Duty Industrial Vacuum



Air Powered Industrial Vacuum



Soot Vacuum



Specifications	VAC-2-15SS	VAC-3A-15SS	AV-1200-15SS	GTC-540-20SS
Motor(s):	Twin	Triple	•	Twin
Motor Power:	2 ² / ₃ HP (Total)	4 HP (Total)	•	2 ¹ / ₄ HP (Total)
Input Power:	18 Amps, 115 V, 50/60 Hz AC Optional 9 Amps, 230 V, 50/60 Hz AC	13.5 Amps, 230 V, 50/60 Hz AC	•	14 Amps, 115 V, 50/60 Hz AC Optional 7 Amps, 230 V, 50/60 Hz AC
Power Supply Cord:	37', 14-3	37', 14-3	•	37', 14-3
Air Requirements:	•	•	Minimum 50 PSI at 35 CFM	•
Static Water Lift:	83"	83"	170" at 90 PSI	50"
Air Displacement:	198 CFM	270 CFM	125 CFM at 90 PSI	270 CFM
Filtration:	15 Microns Polypropylene/Dacron	15 Microns Polypropylene/Dacron	15 Microns Polypropylene/Dacron	15 Microns Polypropylene/Dacron
Tank:	15 Gallons Stainless Steel	15 Gallons Stainless Steel	15 Gallons Stainless Steel	20 Gallons Stainless Steel
Dry Capacity:	14 Gallons	14 Gallons	14 Gallons	20 Gallons
Wet Capacity:	10 Gallons	10 Gallons	10 Gallons	•
Noise Level:	74 dBA	78 dBA	84 dBA	78 dBA
Special Features:	•	•	Air Powered	Polyethylene Tank Liner Disposable Collection Bag
Dimensions:	15" Diameter Tank x 36" High	15" Diameter Tank x 36" High	15" Diameter Tank x 36" High	15" Diameter Tank x 48" High
Weight:	66 Lbs	70 Lbs	58 Lbs	70 Lbs
Accessories/Prices:	See Page 64	See Page 65	See Page 66	See Page 73



VAC-2-15SS



AV-1200-15SS



GTC-540-20SS